NSN 5305-00-889-3153

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-889-3153 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.527 inches and 0.640 inches **Fastener Length:** Between 0.610 inches and 0.640 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.468 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Ams-qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-889-3153

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0