## NSN 5305-00-889-6586

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-889-6586

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
1.500 inches
Head Style:
Flat countersunk
Head Diameter:
0.577 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Thready Qty Per Inch (tpi):
24
24 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:  32.0 microinches threads
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:  32.0 microinches threads  Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Countersink Angle: Between 99.0 degrees and 101.0 degrees  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Countersink Angle: Between 99.0 degrees and 101.0 degrees  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:  32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:  32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, ty2, cl2 federal specification single treatment response
Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Countersink Angle:  Between 99.0 degrees and 101.0 degrees  Surface Finish:  32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416, ty2, cl2 federal specification single treatment response  Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf

N/a

## NSN 5305-00-889-6586

Close Tolerance Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0