NSN 5305-00-890-4654



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-890-4654 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 2.219 inches **Fastener Length:** Between 2.969 inches and 3.031 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.938 inches **Head Height:** Between 0.616 inches and 0.625 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel **Material Specification:** 66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

6 type Shelf Life:

Specification Or Standard:

NSN 5305-00-890-4654

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0