

View Online at <https://aerobasegroup.com/nsn/5305-00-891-1722>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.305 inches and 0.372 inches

**Fastener Length:**

Between 0.627 inches and 0.674 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.376 inches and 0.385 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp h11

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mac ps13145 fscm 76301 mfr ref all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0