## NSN 5305-00-891-1788

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-891-1788 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.060 inches and 1.120 inches **Fastener Length:** Between 1.060 inches and 1.120 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas602 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-891-1788

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.