## NSN 5305-00-891-4896

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-891-4896 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.760 inches **Fastener Length:** Between 1.730 inches and 1.770 inches **Head Style:** Hexagon **Head Height:** Between 0.190 inches and 0.230 inches Width Between Flats: Between 0.480 inches and 0.520 inches **First Diameter From Head:** Between 0.302 inches and 0.322 inches **Second Diameter From Head:** Between 0.230 inches and 0.270 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.115 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.980 inches and 1.020 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel **Material Specification:** Qq-s-763, cl 416, cond a federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-891-4896

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0