NSN 5305-00-891-8989

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-891-8989 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.286 inches **Fastener Length:** Between 0.651 inches and 0.661 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.245 inches and 0.255 inches **First Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 120 degrees of angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Es-337 fscm 53189 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-891-8989

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0