NSN 5305-00-893-1702

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-893-1702 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.660 inches **Head Style:** Flat countersunk **Head Diameter:** 0.430 inches **Shoulder Diameter:** 0.240 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.330 inches first shoulder and 0.340 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 26.0 rockwell c and 34.0 rockwell c **Countersink Angle:** Between 59.0 degrees and 61.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Internally threaded through head no. 4/0.112-40 unc-2b 0.250 min full thd to 0.290 to 0.390 depth countersunk 80-100 degrees 0.120 to 0.140 in. Dia Material: Steel **Material Specification:** Ams 5610 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-893-1702

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0