

View Online at <https://aerobasegroup.com/nsn/5305-00-894-2105>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.260 inches and 0.307 inches

Fastener Length:

1.172 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Locking Feature:

Strip threads

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.044 inches first hole and 1.064 inches first hole

Material:

Steel locking feature

Material Specification:

Mil-s-5000 military specification 1st material response fastener or mil-s-5626 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener

Surface Treatment:

Cadmium grip

Surface Treatment Specification:

Dps9.28, fscm 88277 mfr ref single treatment response grip

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.