## NSN 5305-00-894-4235

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-894-4235 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.727 inches **Fastener Length:** Between 4.156 inches and 4.250 inches **Head Style:** Hexagon **Head Height:** Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.937 inches **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Surface Finish: 63.0 microinches threads Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 2 type and 10p style Shelf Life:

No

N/a

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5305-00-894-4235

Hexagon Head Cap Screw - Page 2 of 2



Fiig:

A003b0