NSN 5305-00-897-7125

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-897-7125 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.859 inches and 0.891 inches **Head Style:** Round **Head Diameter:** Between 0.287 inches and 0.309 inches **Head Height:** Between 0.107 inches and 0.120 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 **Material Specification:** Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-897-7125

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0