NSN 5305-00-899-4499

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-899-4499
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
1.000 inches
Head Style:
Fillister
Head Diameter:
Between 0.389 inches and 0.414 inches
Head Height:
Between 0.161 inches and 0.170 inches
Hole Diameter:
0.062 inches
First Diameter From Head:
0.250 inches
Second Diameter From Head:
Between 0.170 inches and 0.180 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.250 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.750 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Hole Configuration Style:
Round
Externally Relieved Body Diameter Quantity:
1
Special Features:
First diameter from head threaded 1/4-20 unc-2a
Material:

water iai

Stainless steel

NSN 5305-00-899-4499

Externally Relieved Body Screw - Page 2 of 2



Material Specification: 66, 300 series federal standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A003b0