Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-899-4499

View Online at https://aerobasegroup.com/nsn/5305	-00-899-4499
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.250 inches	
Fastener Length:	
1.000 inches	
Head Style:	
Fillister	
Head Diameter:	
Between 0.389 inches and 0.414 inches	
Head Height:	
Between 0.161 inches and 0.170 inches	
Hole Diameter:	
0.062 inches	
First Diameter From Head:	
0.250 inches	
Second Diameter From Head:	
Between 0.170 inches and 0.180 inches	
Distance From Largest Bearing Surface Of Head	To End Of First Diameter:
0.250 inches	
Distance From Largest Bearing Surface Of Head	To End Of Second Diameter:
0.750 inches	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.250 inches	
Hole Quantity:	
1	
Ноlе Туре:	
Drilled	
Thready Qty Per Inch (tpi):	
20	
Hole Configuration Style:	
Round	
Externally Relieved Body Diameter Quantity:	
1	
Special Features:	
First diameter from head threaded 1/4-20 unc-2a	
Material:	
Stainless steel	

NSN 5305-00-899-4499

Externally Relieved Body Screw - Page 2 of 2



Material Specification: 66, 300 series federal standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0