NSN 5305-00-900-3268

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-900-3268

Thread	Class:
2a	

Thread Direction:

Right-hand

Thread Length:

0.188 inches

Fastener Length:

0.188 inches

Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

Head Height:

Between 0.072 inches and 0.079 inches

Hole Diameter:

0.031 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

62000 pounds per square inch

Screw Material:

Aluminum alloy 2024 or aluminum alloy 2017

Screw Material Specification:

Qq-a-200/3 federal specification 1st material response or qq-a-225/6 federal specification 1st material response or qq-a-225/5 federal

specification 2nd material response

Screw Surface Treatment:

Anodize

Screw Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-900-3268

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.

