NSN 5305-00-900-3269

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-900-3269 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.072 inches and 0.079 inches **Hole Diameter:** 0.031 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 or aluminum alloy 2017 **Screw Material Specification:** Qq-a-200/3 federal specification 1st material response or qq-a-225/6 federal specification 1st material response or qq-a-225/5 federal specification 2nd material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-900-3269

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.