

View Online at <https://aerobasegroup.com/nsn/5305-00-901-4408>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.268 inches and 0.346 inches

Fastener Length:

Between 1.167 inches and 1.214 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2487 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Grip Length:

Between 0.750 inches and 0.766 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.095 inches first hole and 1.099 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Retaining element in shank

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.