NSN 5305-00-901-5073

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-901-5073

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.526 inches and 0.609 inches
Fastener Length:
Between 0.609 inches and 0.641 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel fastener
Material Specification:
66 federal standard single material response
Surface Treatment:
Oxide fastener
Surface Treatment Specification:
Mil-c-13924, class 3 military specification single treatment response fastener
Thread Series Designator:
Unc
Specification Data:
80205-nas1352 professional/industrial association standard

NSN 5305-00-901-5073

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-c-13924 spec.

Shelf Life: