

NSN 5305-00-902-1617 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-902-1617 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 

0.164 inches

Width Across Flats:

Between 0.140 inches and 0.142 inches

**Hole Quantity:** 

6

**Hole Type:** 

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

**Hardness Rating:** 

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Steel

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification all treatment responses

## NSN 5305-00-902-1617

Socket Head Cap Screw - Page 2 of 2



Inread Series Designator:	
Unc	
Specification Data:	
80205-nas1352 professional/industrial association standard	
Specification Or Standard:	
6 type	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A003b0