NSN 5305-00-902-4722

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-902-4722

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.342 inches and 0.402 inches
Fastener Length:
Between 0.612 inches and 0.652 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.428 inches and 0.440 inches
Shoulder Diameter:
0.246 inches first shoulder and 0.249 inches first shoulder
Shoulder Length:
0.250 inches first shoulder and 0.270 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-902-4722

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0