

View Online at <https://aerobasegroup.com/nsn/5305-00-903-0728>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.330 inches

**Fastener Length:**

Between 0.590 inches and 0.650 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.380 inches

**Head Height:**

Between 0.080 inches and 0.085 inches

**Shoulder Diameter:**

0.247 inches first shoulder and 0.249 inches first shoulder

**Shoulder Length:**

0.137 inches first shoulder and 0.142 inches first shoulder

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Special Features:**

W/undercut 0.210 in. Min 0.230 in. Maximum dia, 0.050 in. Wide between head and shoulder

**Material:**

Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 8630

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074, cl 1 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-26074 spec.