

View Online at <https://aerobasegroup.com/nsn/5305-00-903-0728>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.330 inches

Fastener Length:

Between 0.590 inches and 0.650 inches

Head Style:

Pan no. 2

Head Diameter:

0.380 inches

Head Height:

Between 0.080 inches and 0.085 inches

Shoulder Diameter:

0.247 inches first shoulder and 0.249 inches first shoulder

Shoulder Length:

0.137 inches first shoulder and 0.142 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Shoulder Shape:

Round first shoulder

Special Features:

W/undercut 0.210 in. Min 0.230 in. Maximum dia, 0.050 in. Wide between head and shoulder

Material:

Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 8630

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074, cl 1 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-26074 spec.