NSN 5305-00-903-5070

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-903-5070

View Online at https://aerobasegroup.com/nsn/5305-00-903-5070
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.122 inches and 0.188 inches
Fastener Length:
Between 0.158 inches and 0.188 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.134 inches and 0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 military specification 2nd material response
or 66 federal standard 4th material response or astm a493 assn standard 5th material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-00-903-5070

Socket Head Cap Screw - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A003b0	

Unit Of Measure:

Mil-std (military Standard):

spec.