## NSN 5305-00-903-7283

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-903-7283 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 3 federal specification all treatment responses

## NSN 5305-00-903-7283

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0