NSN 5305-00-904-5810

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-904-5810

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.313 inches and 0.385 inches |
| Fastener Length: |
| Between 0.365 inches and 0.385 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.250 inches and 0.270 inches |
| Head Height: |
| Between 0.141 inches and 0.156 inches |
| Hole Diameter: |
| Between 0.031 inches and 0.036 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 26.0 rockwell c |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5735 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unjc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Demilitarization: |

No

NSN 5305-00-904-5810 Machine Screw - Page 2 of 2



Fiig:

A500d0