Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-905-5573

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.376 inches |
| Fastener Length: |
| 0.438 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.221 inches and 0.226 inches |
| Head Height: |
| Between 0.134 inches and 0.138 inches |
| Locking Feature: |
| Strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.138 inches |
| Width Across Flats: |
| Between 0.094 inches and 0.095 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Minimum Yield Strength: |
| 30000 pounds per square inch |
| Material: |
| Stainless steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 1 type |

1 type

NSN 5305-00-905-5573

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator:

As modified by locking feature, mil-f-18240; insert to withstand range of minus 320 to plus 390 degrees f

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0