NSN 5305-00-907-3117

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-907-3117 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** 4.172 inches **Head Diameter:** Between 0.216 inches and 0.220 inches **Head Height:** 0.500 inches **Extended Washer Diameter:** 0.250 inches **Extended Washer Thickness:** 0.078 inches First Diameter From Head: 0.125 inches **Second Diameter From Head:** Between 0.161 inches and 0.171 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 3.530 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.718 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se **Material Specification:** Qq-s-763 cond b federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-907-3117

Externally Relieved Body Screw - Page 2 of 2



--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.