## NSN 5305-00-907-3298

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-907-3298 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.225 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.085 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** 30302 assn standard single material response or 30303 assn standard single material response or 30304 assn standard single material response or 30305 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-00-907-3298

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0