NSN 5305-00-908-4503

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-908-4503 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.330 inches **Fastener Length:** Between 0.402 inches and 0.412 inches **Head Diameter:** 0.375 inches **Head Height:** Between 0.388 inches and 0.398 inches **Extended Washer Diameter:** 0.625 inches **Extended Washer Thickness:** 0.098 inches **Shoulder Diameter:** 0.625 inches first shoulder **Shoulder Length:** 0.098 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Shoulder Shape:** Round first shoulder **Special Features:** Heat treat to 125-145, 000 psi Material: Steel comp 8630 or steel comp 4130 **Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-6758 military specification 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-908-4503

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.