NSN 5305-00-909-6117



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-909-6117 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.450 inches **Fastener Length:** Between 0.730 inches and 0.732 inches **Head Style:** Flat chamfer **Head Diameter:** 0.625 inches **Head Height:** Between 0.100 inches and 0.120 inches **Shoulder Diameter:** 0.480 inches first shoulder and 0.490 inches first shoulder **Shoulder Length:** 0.270 inches first shoulder and 0.290 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 40.0 rockwell c and 45.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 **Material Specification:** Mil-s-5626 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-00-909-6117

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.