## NSN 5305-00-909-6118

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-909-6118 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.460 inches **Fastener Length:** Between 0.980 inches and 1.040 inches **Head Style:** Flat chamfer **Head Diameter:** 1.125 inches **Head Height:** Between 0.100 inches and 0.130 inches **Shoulder Diameter:** 0.872 inches first shoulder and 0.873 inches first shoulder **Shoulder Length:** 0.285 inches first shoulder and 0.295 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 **Surface Treatment:** Phosphate manganese or phosphate zinc

**Surface Treatment Specification:** 

Mil-p-16232 ty m cl 1 military specification 1st treatment response or mil-p-16232 ty m cl 2 military specification 2nd treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A003b0

## NSN 5305-00-909-6118

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-p-16232 spec.