## NSN 5305-00-911-3837

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-911-3837 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.077 inches and 0.082 inches **Fastener Length:** 0.254 inches **Head Style:** Hexagon **Head Height:** 0.050 inches Width Between Flats: Between 0.240 inches and 0.250 inches **First Diameter From Head:** Between 0.240 inches and 0.250 inches **Second Diameter From Head:** Between 0.183 inches and 0.189 inches Third Diameter From Head: Between 0.095 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.025 inches and 0.035 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.103 inches and 0.113 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.135 inches and 0.145 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Copper alloy 360 **Material Specification:** Qq-b-611 1/4 hard federal specification single material response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-911-3837

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0