## NSN 5305-00-912-5836

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-912-5836



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.235 inches and 0.265 inches
Fastener Length:
Between 0.297 inches and 0.327 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Stainless steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5305-00-912-5836

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

