NSN 5305-00-912-6254

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-912-6254 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.110 inches **Fastener Length:** 0.310 inches **Head Style:** Fillister **Head Diameter:** Between 0.168 inches and 0.183 inches **Head Height:** Between 0.070 inches and 0.072 inches **Hole Diameter:** 0.037 inches First Diameter From Head: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.170 inches and 0.230 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 55000 pounds per square inch **Hole Configuration Style:** Round **Externally Relieved Body Diameter Quantity:** Material: Steel

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or qq-z-323 type 2 cl 3 federal specification 2nd treatment response

NSN 5305-00-912-6254

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0