## NSN 5305-00-912-7308

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-912-7308



#### Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.376 inches and 0.515 inches

## Fastener Length:

Between 0.891 inches and 0.938 inches

### Head Style:

Pan

## Head Diameter:

Between 0.357 inches and 0.373 inches

## Head Height:

Between 0.122 inches and 0.133 inches

## Internal Drive Style:

Cross recess type 1

### Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### **Screw Material:**

Steel comp 8630 or steel comp 4037

#### Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

#### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-912-7308

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

