# NSN 5305-00-912-7658

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-912-7658



#### **Thread Class:**

2a

**Thread Direction:** 

Right-hand

# Thread Length:

Between 0.208 inches and 0.250 inches

## Fastener Length:

Between 0.219 inches and 0.250 inches

### Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

# Head Height:

Between 0.072 inches and 0.079 inches

# Hole Diameter:

# 0.037 inches

Internal Drive Style:

Slot

#### **Thread Diameter:**

0.112 inches

### Hole Quantity:

1

#### Thready Qty Per Inch (tpi):

48

#### Min. Tensile Strength (psi):

80000 pounds per square inch

#### **Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

#### Screw Material Specification:

66 federal standard all material responses

#### Screw Surface Treatment:

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Head Hole Configuration Style:

Round

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5305-00-912-7658

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

