

View Online at <https://aerobasegroup.com/nsn/5305-00-914-3818>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.418 inches and 0.438 inches

Fastener Length:

Between 0.923 inches and 0.933 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.419 inches and 0.437 inches

Head Height:

Between 0.209 inches and 0.219 inches

Shoulder Diameter:

0.3085 inches first shoulder and 0.3105 inches first shoulder

Shoulder Length:

0.495 inches first shoulder and 0.505 inches first shoulder

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0