NSN 5305-00-914-3819

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-914-3819 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.418 inches and 0.438 inches **Fastener Length:** Between 1.173 inches and 1.183 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.209 inches and 0.219 inches **Shoulder Diameter:** 0.3085 inches first shoulder and 0.3105 inches first shoulder **Shoulder Length:** 0.745 inches first shoulder and 0.755 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-00-914-3819

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0