

View Online at <https://aerobasegroup.com/nsn/5305-00-914-3820>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.418 inches and 0.438 inches

**Fastener Length:**

Between 1.658 inches and 1.698 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.419 inches and 0.437 inches

**Head Height:**

Between 0.209 inches and 0.219 inches

**Shoulder Diameter:**

0.3085 inches first shoulder and 0.3105 inches first shoulder

**Shoulder Length:**

1.147 inches first shoulder and 1.167 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.156 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0