NSN 5305-00-914-3821

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-914-3821

view Online at https://aerobasegroup.com/hsr/>3505-00-914-3621
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.480 inches and 0.500 inches
Fastener Length:
Between 0.970 inches and 1.010 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.543 inches and 0.562 inches
Head Height:
Between 0.240 inches and 0.250 inches
Shoulder Diameter:
0.371 inches first shoulder and 0.373 inches first shoulder
Shoulder Length:
0.397 inches first shoulder and 0.417 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.188 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-00-914-3821

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0