## NSN 5305-00-914-4168



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-914-4168 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.720 inches and 0.750 inches **Fastener Length:** Between 3.470 inches and 3.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.853 inches and 0.875 inches **Head Height:** Between 0.365 inches and 0.375 inches **Shoulder Diameter:** 0.621 inches first shoulder and 0.623 inches first shoulder **Shoulder Length:** 2.750 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-00-914-4168

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0