NSN 5305-00-914-4172

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-914-4172 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.480 inches and 0.500 inches **Fastener Length:** Between 1.485 inches and 1.495 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.543 inches and 0.562 inches **Head Height:** Between 0.244 inches and 0.250 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.373 inches first shoulder **Shoulder Length:** 1.495 inches first shoulder and 1.505 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-00-914-4172

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0