

View Online at <https://aerobasegroup.com/nsn/5305-00-914-4173>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.480 inches and 0.500 inches

**Fastener Length:**

Between 2.985 inches and 2.995 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.543 inches and 0.562 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Shoulder Diameter:**

0.371 inches first shoulder and 0.373 inches first shoulder

**Shoulder Length:**

2.495 inches first shoulder and 2.505 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

0.188 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0