Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-914-6138



2a Thread Direction: Right-hand Thread Length: Between 1.500 inches and 1.719 inches Fastener Length: Between 3.150 inches and 3.250 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Right-hand Thread Length: Between 1.500 inches and 1.719 inches Fastener Length: Between 3.150 inches and 3.250 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Thread Length: Between 1.500 inches and 1.719 inches Fastener Length: Between 3.150 inches and 3.250 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Between 1.500 inches and 1.719 inches Fastener Length: Between 3.150 inches and 3.250 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Fastener Length:Between 3.150 inches and 3.250 inchesHead Style:HexagonHead Height:Between 0.378 inches and 0.403 inchesWidth Between Flats:Between 0.922 inches and 0.938 inches
Between 3.150 inches and 3.250 inches Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Head Style: Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Hexagon Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Head Height: Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.922 inches and 0.938 inches
Width Between Flats: Between 0.922 inches and 0.938 inches
Between 0.922 inches and 0.938 inches
Hole Diameter:
0.094 inches
Thread Diameter:
0.625 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 38.0 rockwell c
Minimum Yield Strength:
120000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Material:
Steel
Material Specification:
Sae gr 8 assn standard single material response
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 type 2 sc 3 assn standard single treatment response
Thread Series Designator:
Unf

NSN 5305-00-914-6138

Hexagon Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

