NSN 5305-00-915-2560

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-915-2560



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.291 inches and 0.341 inches Fastener Length: Between 0.489 inches and 0.519 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.133 inches and 0.150 inches Hole Diameter: Between 0.060 inches and 0.068 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.178 inches and 0.198 inches **Hole Quantity:** 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate

NSN 5305-00-915-2560

Close Tolerance Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1124 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0