NSN 5305-00-915-2570

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-915-2570 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.280 inches and 0.337 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy **Material Specification:** Nas621, 6al-4v assn standard single material response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1152 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-915-2570

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0