NSN 5305-00-915-2582

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-915-2582

| Thread Class: |
|--|
| 3a |
| Sa Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| 0.276 inches |
| Fastener Length: |
| Between 1.449 inches and 1.479 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.328 inches and 0.385 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 1.188 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Nas 621, 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| - |
| 80205-nas1153 professional/industrial association standard Shelf Life: |
| |
| |
| Unit Of Measure: |
| |

NSN 5305-00-915-2582

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

