NSN 5305-00-915-2610

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-915-2610

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.511 inches and 0.541 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.118 inches and 0.296 inches
Head Height:
Between 0.103 inches and 0.118 inches
Hole Diameter:
0.038 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.192 inches
Grip Length:
0.250 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 321.0 brinell standard
Hole Configuration Style:
Round
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response

NSN 5305-00-915-2610

Close Tolerance Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Uns
Specification Data:
80205-nas1123 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0