NSN 5305-00-916-4621

Machine Screw - Page 1 of 1



05-00-916-4621

| Machine Screw - Page 1 of 1 | |
|--|----|
| View Online at https://aerobasegroup.com/nsn/530 |): |
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.868 inches | |
| Fastener Length: | |
| 2.306 inches | |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 1.024 inches and 1.034 inches | |
| Internal Drive Style: | |
| High-torque | |
| Thread Diameter: | |
| 0.625 inches | |
| Thready Qty Per Inch (tpi): | |
| 18 | |
| Hardness Rating: | |
| Between 46.0 rockwell c and 50.0 rockwell c | |
| Countersink Angle: | |
| 60.0 degrees | |
| Screw Material: | |
| Steel comp h11 | |
| Screw Material Specification: | |
| Ams 6485 assn standard single material response | |
| Screw Surface Treatment: | |
| Nickel and cadmium | |
| Thread Series Designator: | |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A500d0 | |
| | |
| | |