## NSN 5305-00-916-6520



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-916-6520 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.316 inches **Fastener Length:** Between 0.801 inches and 0.831 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.133 inches and 0.150 inches **Hole Diameter:** 0.064 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** 0.500 inches **Hole Quantity:** 2 **Hole Type:** Drilled 248.0 brinell standard and 321.0 brinell standard

Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating: Hole Configuration Style:** Round **Surface Finish:** 32.0 microinches threads **Product Name:** 

Navy special project

Material: Iron alloy 660

## NSN 5305-00-916-6520

Close Tolerance Screw - Page 2 of 2



Material Specification:
Ams 5735 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1124 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0