NSN 5305-00-916-6688

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-916-6688

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.291 inches and 0.341 inches |
| Fastener Length: |
| Between 0.551 inches and 0.581 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.449 inches and 0.507 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas1154 professional/industrial association standard |
| Shelf Life: |
| N/a |
| |

NSN 5305-00-916-6688

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

